

## Data sheet

### PRODUCT SPECIFICATION

Name				<b>Eazy Timber</b> WPC Square Hollow Decking
Style/Item No.				zu-146H24
Density				1310kg/m <sup>3</sup>
End use application				outdoor flooring
Composition				PE plastic, wood powder and additives, such as UV stabilisers, anti oxidant, coupling agents, pigments and lubricants etc.
Thickness	EN ISO	24346		24mm
Lenght/Width	EN ISO	24341		2400mmx146mm
Weight	EN ISO	23997		2800g/m

### CLASSIFICATION

Fire Rating	EN 13501	Class	B-S1
Toxic Testing	GB18586-2001	-	Good
Electrical Resistance	EN1081	Ω	>3.0*10 <sup>10</sup>
Slip Resistance Dry	EN15534	CEN/TS 15676:2007	79
Slip Resistance Wet	EN15534	CEN/TS 15676:2007	72

### PRODUCT PERFORMANCE

Dimensional stability	EN15534-1:2014	%	≤0.3
Swelling and water absorption	EN317:1993	%	5.0
Thermal Conductivity	EN12667	W/(m.k)	0.050
Castor Wheel Test	EN425	-	SUITABLE
Wear Resisitance	EN660.2	mm <sup>3</sup>	≤3.5
Abrasion Group	EN649	group	p
Residual Indentation	EN ISO 24343.1	mm	About 0.04
Colour Fastness	ASTM G154	Scale	3
Chemical Product Resisitance	EN ISO 26987	-	GOOD
Antibacterial Property	EN ISO 846-C	-	No bacterial grow
Hygiene Treatment	MRSA	-	VERY GOOD
Impact Sound Redution	EN ISO 10140/1 EN ISO 717/2	-	APPROX.+4DB
Surfece Treatment	-	-	PUR